



MLED-180HI Ex

External Powered Marine Lantern

MLED-180HI Ex brings the benefits of LED technology, low power, high reliability and low maintenance, to the Zone 1 environment. The flasher and optical source assembly designated MaxiHALO-180HI is designed after the proven MaxiHALO-150.

The MaxiHALO-180HI is installed in a rugged Exd well glass housing used in the rigours of offshore atmospheres. When used in a biform arrangement a range of in excess of 15NM is achieved. Onboard software constantly monitors operation of the MLED-180HI Ex and initiates an alarm signal if critical operation parameters are exceeded.

FEATURES

MLED-180HI Ex

- User selectable power settings
- 256 user selectable flash characters
- Temperature compensated LED drive circuits ensure uniform brightness with changes in ambient temperature
- Full monitor and control capability
- Fail output terminal for go/no go monitoring
- Constant current power source maximises LED life




SPECIFICATIONS

| | |
|---------------------------|--|
| Input Voltage | 24VDC |
| Average Power Consumption | <40W |
| Quiescent Current | <7mA |
| Visibility | 360° horizon (omnidirectional) |
| Monitor and Control | Capable |
| Flash Codes | 256 codes |
| Synchronisation | Hardwire |
| Sunswitch Threshold | Variable |
| Weight | 15kg (33lb) |
| Operating Temperature | -40° C to +60° C |
| Relative Humidity | 100% Condensing |
| Atmosphere | Rated for operation in salt air |
| Wind | Designed to withstand speeds in excess of 320kmph (200mph) |
| IP Rating | IP66 |
| Protection | II2 GD EEx de IIC T3 |
| Base | Cast Aluminium |
| Outer Lens | Tempered Glass |

NOTE: Specifications are subject to change.

MLED-180HI Ex

MEETS THE STRICT REQUIREMENTS
OF THE NORTH SEA PLATFORMS



USA - HOUSTON
P: + 1 713 681 6101
F: + 1 713 681 6233
E: us-sales@tidelandsignal.com

CANADA - DSS MARINE
P: + 844 843 3526
F: + 613 680 7418
E: canada-sales@tidelandsignal.com

UK - BURGESS HILL
P: + 44 (0) 1444 872240
F: + 44 (0) 1444 872241
E: emea-sales@tidelandsignal.com

UK - GT YARMOUTH
P: + 44 (0) 1493 441711
F: + 44 (0) 1493 440322
E: emea-sales@tidelandsignal.com

UAE - DUBAI
P: + 971 (0) 4 885 5842
F: + 971 (0) 4 885 7352
E: emea-sales@tidelandsignal.com

SINGAPORE
P: + 65 6333 0078
F: + 65 6333 0079
E: asia-sales@tidelandsignal.com

CHINA
P: + 86 (0) 1380 101 4639
F: + 86 (0) 21 3868 8087
E: asia-sales@tidelandsignal.com

ISO 9001:2008
Certificate
Number: 30061

