



SolaMAX-65

Class 5 and 7 Self-Contained Lantern


The SolaMAX-65 is a self-contained lantern capable of ranges up to 5NM in the standard version and up to 7NM in the extended version (SolaMAX-65-T). Its compact design makes it the ideal self-contained lantern for many applications including inland waterways, buoys and offshore platform marking to provide years of maintenance-free operation. Revolutionary optics and high efficiency solar panels make the SolaMAX-65 exceptionally suitable for northern and southern latitudes and low solar radiation applications.

The built-in IR receiver allows for full customisation of the power level, flash character, sunswitch setting and features a self test mode. A convenient magnetic switch is used for switching off, storage/sleep mode or regular operation.

SolaMAX-65

FEATURES

- Options of battery capacity for demanding locations from 12Ah to 50Ah
- Optional GPS synchronisation module
- Available in all IALA approved colours
- 256 user selectable flash characters
- Constant current power source for maximum LED life
- Magnetic On/Off Switch for quick deployment, hassle free storage and battery maintenance check
- User selectable power, flash character and sunswitch settings via an optional IR controller
- Programming and self test option with IR controller
- Full monitor and control capability via options of GSM, Satellite or AIS
- Internal AIS option with no exterior VHF or GPS antennas
- Theft deterrent design



30°


120°

SPECIFICATIONS

Voltage	12VDC
Power Setting	Field Selectable
Visibility	360° horizon (omnidirectional)
Vertical Divergence	5°, 10°, 20° or 30° degrees at 50%; ± 1 degree
Control	Via IR programmer
Monitor	Options of GSM, Satellite or AIS
Flash Codes	Up to 256 codes, field selectable or via communication link
Synchronisation	GPS or hardwire options
Solar Panels	Standard 4 x 4.2W, "T" model 4 x 8.5W
Battery Capacity - Standard	12Ah or 18Ah Sealed Lead Acid
Battery Capacity - "T" model	"T" model 30Ah or 50Ah Sealed Lead Acid
Operating Temperature	-40°C to +70°C
Size - Standard	275mm (10.8in) wide x 315mm (12.4in) high
Size - "T" model	275mm (10.8in) wide x 448mm (17.6in) high
Weight - Standard	Standard with 12Ah 7.8kg (17.1lb), with 18Ah 9.5kg (20.9lb)
Weight - "T" model	"T" model with 30Ah 15.7kg (34.5lb), with 50Ah 20.2kg (44.5lb)
Mounting	12 x 16mm (0.63in) x 25mm (0.98in) slots on 200mm (9.1in) bolt hole circle
IP Rating	IP 66 and IP 68

NOTE: Specifications are subject to change.

SolaMAX-65 Self-Contained Lantern



USA - HOUSTON
P: + 1 713 681 6101
F: + 1 713 681 6233
E: us-sales@tidelandsignal.com

CANADA - DSS MARINE
P: + 844 843 3526
F: + 613 680 7418
E: canada-sales@tidelandsignal.com

UK - BURGESS HILL
P: + 44 (0) 1444 872240
F: + 44 (0) 1444 872241
E: emea-sales@tidelandsignal.com

UK - GT YARMOUTH
P: + 44 (0) 1493 441711
F: + 44 (0) 1493 440322
E: emea-sales@tidelandsignal.com

UAE - DUBAI
P: + 971 (0) 4 885 5842
F: + 971 (0) 4 885 7352
E: emea-sales@tidelandsignal.com

SINGAPORE
P: + 65 6333 0078
F: + 65 6333 0079
E: asia-sales@tidelandsignal.com

CHINA
P: + 86 (0) 158 0223 7983 (primary)
P: + 86 (0) 138 0101 4639
E: asia-sales@tidelandsignal.com