



TRB-220

MaxLumina® Rotating Beacon

TRB-220 is a high intensity rotating beacon capable of providing simple and complex flash characters. This beacon can be configured to provide high efficiency in effective intensities using a wide range of low wattage marine signal lamps as well as LED light source.

Tideland Signal's TRB-220 MaxLumina® is excellent in battery operations where a proper charge level can be maintained through photovoltaic charging from solar panels. A 6-lens carousel, light source, gearless direct drive motor and electronic control module are contained in a watertight aluminium and fiberglass housing (IP65) with acrylic glazing and stainless steel fasteners.

Mounted on a light tower of proper height, TRB-220 gives coastal shipping up to a 20NM range light (@ T = 0.74).

FEATURES

- 6-lens carousel, consisting of a flash panel design with catadioptric prisms
- Operates with up to a 110W lamp without need for ventilation or cooling fans
- Brushless DC direct drive motor designed for smooth operation at low RPM
- Over 16 preprogrammed rotation periods, ranging from a period of 6 to 120 seconds
- 25 years of useful life
- Available in all IALA colours
- No scheduled maintenance for life of motor
- Accommodates Tideland's TF-3B MicroPower OMNIBUS® II 6-place lampchanger, MaxiHALO-60RB (LED) or MLED-Retro
- Automatic switchover to standby lantern
- Full monitor and control access



SPECIFICATIONS

Power Consumption Lamp version LED version Motor	As specified (from 3 to 110W) Up to 30W Average 2.5W
Power Input DC Version AC Version (requires additional equipment)	9 – 36VDC 110 – 240VAC, 50/60Hz
Light Source	Tideland TF-3B OMNIBUS® II, high temperature, 3 or 6 place lampchanger, MaxiHALO-60RB (LED) or MLED-Retro
Drive System	Brushless DC motor; gearless direct drive
Optics Acrylic Moulded Flash Panel Glazing	110mm focal length, Catadioptric Fresnel Lens 330mm UV-resistant acrylic
Lens Configuration Standard	220mm Hexagonal
Ventilation	Not required (up to 110W bulb)
Rotation Periods	16 rotation periods, field selectable Standard Periods 120, 90, 72, 60, 48, 40, 30, 24, 20, 15, 12, 10, 9, 8, 7 and 6 seconds
Environmental Temperature Humidity	-40° C to +55° C 100% non-condensing
Physical Size Height Weight	851mm (33.5in) with spike 20.5kg (45lb)
IP Rating	IP65

NOTE: Specifications are subject to change.

TRB-220

**A PROVEN AND RELIABLE
DESIGN THAT HAS STOOD THE
TEST OF TIME**

TRB-220 ROTATING BEACON. HEXAGONAL LENS CAROUSEL CONFIGURATION

LAMP SIZE	HOR. DIV. (deg)	FIXED INT.** (cd)	ROTATION PERIOD / SPEED							
			120 sec / 0.5 rpm	90 sec / .666 rpm	72 sec / .833 rpm	60 sec / 1.0 rpm	48 sec / 1.25 rpm	40 sec / 1.5 rpm	30 sec / 2.0 rpm	24 sec / 2.5 rpm
12 V / 10 W On-Time, Sec	160°	42,724	21,987 0.533	18,936 0.400	16,616 0.320	14,803 0.267	12,724 0.213	11,157 0.178	8,952 0.133	7,475 0.107
12 V / 20 W On-Time, Sec	153°	109,561	58,509 0.51	50,670 0.383	44,652 0.306	39,912 0.255	34,438 0.204	30,285 0.170	24,400 0.128	20,430 0.102
12 V / 35 W On-Time, Sec	193°	169,903	104,364 0.643	92,516 0.483	83,033 0.386	75,313 0.322	66,111 0.257	58,914 0.214	48,379 0.161	41,040 0.129
12 V / 50 W On-Time, Sec	190°	241,131	145,260 0.633	128,321 0.475	114,848 0.380	103,935 0.317	90,993 0.253	80,916 0.211	66,245 0.158	56,077 0.127
12 V / 75 W On-Time, Sec	235°	238,643	148,914 0.783	132,388 0.588	119,092 0.470	108,223 0.392	95,214 0.313	84,997 0.261	69,979 0.196	59,471 0.157
12 V / 100 W On-Time, Sec	240°	367,823	238,459 0.800	213,526 0.600	193,204 0.480	176,414 0.400	156,105 0.320	139,990 0.267	116,032 0.200	99,077 0.160

LAMP SIZE	HOR. DIV. (deg)	FIXED INT.** (cd)	ROTATION PERIOD / SPEED							
			20 sec / 3.0 rpm	15 sec / 4.0 rpm	12 sec / 5.0 rpm	10 sec / 6.0 rpm	9 sec / 6.66 rpm	8 sec / 7.5 rpm	7 sec / 8.57 rpm	6 sec / 10.0 rpm
12 V / 10 W On-Time, Sec	160°	42,724	6,416 0.089	5,000 0.067	4,096 0.053	3,469 0.044	3,150 0.040	2,821 0.036	2,489 0.031	2,151 0.027
12 V / 20 W On-Time, Sec	153°	109,561	17,571 0.085	13,729 0.064	11,265 0.051	9,551 0.043	8,680 0.038	7,777 0.034	6,867 0.030	5,938 0.026
12 V / 35 W On-Time, Sec	193°	169,903	35,635 0.107	28,205 0.080	23,339 0.064	19,905 0.054	18,143 0.048	16,306 0.043	14,443 0.038	12,530 0.032
12 V / 50 W On-Time, Sec	190°	241,131	48,615 0.106	38,397 0.079	31,728 0.063	27,033 0.053	24,627 0.048	22,122 0.042	19,584 0.037	16,981 0.032
12 V / 75 W On-Time, Sec	235°	238,643	51,707 0.131	41,000 0.098	33,968 0.078	28,994 0.065	26,439 0.059	23,773 0.052	21,067 0.046	18,285 0.039
12 V / 100 W On-Time, Sec	240°	367,823	86,445 0.133	68,881 0.100	57,249 0.080	48,978 0.067	44,714 0.060	40,254 0.053	35,716 0.047	31,040 0.040

Effective Intensity Table for Selected Rotation Periods (All Calculations were made with the Schmidt-Clausen Method)

****NOTES:**

- All fixed intensities were measured with the outer glazing in place.
- The Schmidt-Clausen Formula is used in compliance with IALA's "Recommendation for the Calculation of the Effective Intensity of a Rhythmic Light", November 1980.
- Intensities may be reduced due to shadowing when using a 6-place lampchanger by approximately 20% at two small arcs 180° apart.

USA - HOUSTON
P: + 1 713 681 6101
F: + 1 713 681 6233
E: us-sales@tidelandsignal.com

CANADA - DSS MARINE
P: + 844 843 3526
F: + 613 680 7418
E: canada-sales@tidelandsignal.com

UK - BURGESS HILL
P: + 44 (0) 1444 872240
F: + 44 (0) 1444 872241
E: emea-sales@tidelandsignal.com

UK - GT YARMOUTH
P: + 44 (0) 1493 441711
F: + 44 (0) 1493 440322
E: emea-sales@tidelandsignal.com

UAE - DUBAI
P: + 971 (0) 4 885 5842
F: + 971 (0) 4 885 7352
E: emea-sales@tidelandsignal.com

SINGAPORE
P: + 65 6333 0078
F: + 65 6333 0079
E: asia-sales@tidelandsignal.com

CHINA
P: + 86 (0) 1380 101 4639
F: + 86 (0) 21 3868 8087
E: asia-sales@tidelandsignal.com



MaxLumina® and MicroPower OMNIBUS® are registered trademarks of Tideland Signal Corporation.
© Tideland Signal Corporation 2015
B13R05